

Specifications:**GHB-1340A**

Stock Number.....321357A

Capacities:

Swing Over Bed..... 13"
 Swing Over Cross Slide.....7-25/32"
 Swing Through Gap..... 18-3/4"
 Length of Gap..... 8-1/8"
 Distance Between Centers..... 40"

Headstock:

Hole Through Spindle 1-1/2"
 Spindle Nose D1-4
 Taper in Spindle Nose MT-5
 Spindle Taper Adapter MT-3
 Spindle Bearing Type..... Taper Roller Bearing
 Number of Spindle Speeds8
 Range of Spindle Speeds 70-2000 RPM

Gearbox:

Number of Longitudinal and Cross Feeds22/22
 Range of Longitudinal Feeds (inch/rev)..... 0.0018" - 0.0325"
 Range of Cross Feeds (inch/rev)..... 0.0006" - 0.0112"
 Number of Inch Threads 38
 Range of Inch Threads 3-1/2 - 80 TPI
 Number of Metric Threads23
 Range of Metric Threads..... 0.45 - 10mm
 Leadscrew 7/8" x 8 TPI
 Feed Rod Diameter3/4"

Compound and Carriage:

Toolpost Type..... 4-Way
 Maximum Tool Size 5/8" x 5/8"
 Maximum Compound Slide Travel.....2-11/16"
 Maximum Cross Slide Travel 6-5/16"
 Maximum Carriage Travel..... 35"

Tailstock:

Tailstock Spindle Travel..... 3-3/4"
 Diameter of Tailstock Spindle..... 1-1/4"
 Taper in Tailstock Spindle..... MT-3

Miscellaneous:

Steady Rest Capacity 1/4" - 2-5/8"
 Follow Rest Capacity 1/4" - 2 -3/4"
 Length of Bed 54"
 Width of Bed..... 7-3/8"
 Height of Bed..... 12"
 Overall Dimensions..... 73-2/3"L x 30"W x 25-1/2"H
 Main Motor2HP, 1Ph
 230V only
 Net Weight (approx.)..... 1,070 lbs.
 Shipping Weight (approx.)..... 1,280 lbs.